OLIVE 707
SILIKONIZOVANÝ AKRYLOVÝ TMEL

Declaration of performance

In accordance with Annex III of Regulation (EU) No 305/2011 amended by Commission Delegated Regulation (EU) No 574/2014

Nr.: OQ-3016223

CE

- **Unique identification code of the product-type:**

  OLIVE 707 SILIKONIZOVANÝ AKRYLOVÝ TMEL

- **Intended use/uses:**

  Non-structural elastic sealant intended for sealing facade elements in building construction, including the interior face:

  EN 15651-1; **type F-EXT-INT, class 7,5P**

- **Manufacturer:**

  WOLF GROUP IBÉRICO S.A.U.
  Av. Bertrán Güell, 78.
  E-08850 GAVÁ (Barcelona)
  SPAIN

- **System or systems of assessment and verification of constancy of performances (AVCP):**

  System 3 for the type testing.

  System 3 for the reaction to fire.

- **Harmonised standard:**

  EN 15651-1 :2012

  Notified body/ies:

  1292 - FUNDACION TECNALIA RESEARCH & INNOVATION

Wolf Group

- ## Declared performance/s:

Essential characteristics	Declared Performance	Harmonised technical specification
Reaction to fire: (EN 13501-1:2007 + A1:2010)	Class E	EN 15651-1 :2012
Release of chemicals dangerous to the environment and health:	See product safety data sheet	
Water tightness and air tightness as determined by:		
• Resistance to flow (EN ISO 7390)	≤ 3 mm	
• Loss of volume (EN ISO 10563)	≤ 25 %	
• Tensile properties (i.e. elongation at break) after water immersion (EN ISO 10591)	≥ 25%	
Durability:	Pass	

Conditioning: Method A (according to ISO 8340)
Substrates: Anodized aluminium without primer.

- ## Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Gavà, Barcelona (Spain)
19 / 04 / 2024

José M. Martínez
R&D Manager
WOLF GROUP IBÉRICO S.A.U.

Disclaimer: The information contained in this DoP is provided in good faith and deemed accurate at the date of publication of this document. Despite the intended uses specified in this document and due to the different conditions of use, the user is obliged to ensure the product is suitable for its particular application and is legally compliant for it. This information should not be construed as legal advice. Wolf Group Ibérico S.A.U. makes no warranty express or implied regarding the fitness of the Product for any particular purpose. It is over understood that we warranty the irreproachable quality of our products in accordance with our General Conditions of Sales and Supply.

Wolf Group

CE MARKING

OLIVE 707 SILIKONIZOVANÝ AKRYLOVÝ TMEL

CE

1292

WOLF GROUP IBÉRICO S.A.U., Av. Bertrán Güell, 78,
08850 Gavà (Barcelona), Spain.

16

OQ-3016223

EN 15651-1:2012: F-EXT-INT, class 7,5P

OLIVE 707 SILIKONIZOVANÝ AKRYLOVÝ TMEL

Sealant for facade elements (exterior and interior).

Conditioning:	Method A
Substrates:	Anodized aluminium without primer.

REACTION TO FIRE:	Class E
RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH:	See product safety data sheet
WATER TIGHTNESS AND AIR TIGHTNESS AS DETERMINED BY:	
• Resistance to flow:	≤ 3 mm
• Loss of volume:	≤ 25%
• Tensile properties at elongation at break after water immersion:	≥ 25%
DURABILITY:	Pass

www.rover-lbc.cz/pov

Wolf Group